

SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: TRANSENE COMPANY, INC.
ADDRESS: DANVERS INDUSTRIAL PARK
10 ELECTRONICS AVENUE DANVERS, MA 01923
TEL: (978) 777-7860 FAX: (978)-739-5640
WWW.TRANSENE.COM
EMERGENCY NO. 1-800-424-9300 CHEMTREC

MATERIAL NAME: **Aluminum Etchant Type D**

REVISED: July 2013

CHEMICAL FAMILY: Acid mixture

Product Number: 060-ALUMD

SECTION 2. HEALTH HAZARD INFORMATION

Hazard Statements

H290 Corrosive to Metals: Category 1

H303 Acute toxicity Oral : Category 5

H313 Acute toxicity Dermal: Category 5

H331 Acute toxicity Inhalation : Category 3

H314 Skin corrosion / Skin irritation : Category 1

H318 Serious eye damage / Eye irritation : Category 1

H371 Special target organ systemic toxicity single exposure: Category 2

H373 Special target organ systemic toxicity repeated exposure : Category 2

Pictograms or Hazard symbols



Warning: May be corrosive to metals



Harmful if swallowed or in contact with skin.



Danger: Toxic if mist is inhaled.



Danger: Causes severe skin burns and serious eye damage.



Warning. Health hazard. May cause damage to lungs, eyes, and mucous membranes through prolonged or repeated exposure.

Precautionary Statements

- P234 Keep only in original container.
- P260 Do not breathe fume/gas/mist/vapors.
- P261 Avoid breathing fumes/mist/vapors.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink, or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves, clothing, and eye and face protection.
- P301 + P330 + P331 If swallowed, rinse mouth. Do not induce vomiting.
- P303 + P361 + P353 If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water.
- P304 + P340 If inhaled, remove person to fresh air and keep comfortable for breathing.
- P305 + P351 + P338 If in eyes, rinse cautiously with water for several minutes.
- P308 + P311 If exposed or concerned, call a physician.
- P311 Seek medical assistance if not breathing.
- P312 Call a physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P363 Wash contaminated clothing before reuse.
- P390 Absorb spillage to prevent material damage.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P406 Store in corrosive resistant container.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3.COMPOSITION/INFORMATION ON INGREDIENTS

Material		Wt %	Toxicity
Sodium-M-Nitrobenzene Sulfonate	CAS#127-68-4	5-10	2300 mg/m ³
Phosphoric Acid	CAS# 7664-38-2	55-65	1 ppm
Acetic Acid	CAS# 64-19-7	1-5	10 ppm
Water	CAS# 7732-18-5	20-39	
Total			

SECTION 4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

FIRST AID:

Eye Contact: Corrosive to naked eye; in case of contact flush eyes well for 15 minutes, lifting the lower and upper eyelids occasionally. May cause blindness. Seek medical attention.

Skin Contact: Obtain medical attention: Corrosive to exposed skin. Flush skin well with water for 15 minutes, wash with soap and water. Remove affected clothing, get medical attention.

Inhalation: If mist or fumes are inhaled, remove to fresh air. If not breathing give artificial respiration. Seek medical attention. Effects may be delayed. May cause chemical burns to the respiratory tract.

Ingestion: May cause severe and permanent damage to the digestive tract. Causes gastrointestinal burns and perforation of the digestive tract. Get medical attention immediately.

SECTION 5. FIRE FIGHTING MEASURES

Flash Point and Method	Autoignition Temp.	Flammability Limits In Air	<u>LOWER</u>	<u>UPPER</u>
non-flammable	NA		NA	NA

Extinguishing media: Water spray or fog, carbon dioxide and dry chemical. Do not use organic media.

Special fire fighting procedures: Wear chemically retardant gear and NIOSH approved self-contained breathing apparatus. Thermal decomposition produces irritating and toxic fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILLS, LEAKS: Ventilate area of leak or spill. Clean up personnel should wear protective clothing and NIOSH approved respirator. Dike and cover the contaminated areas with absorbent, non-combustible material such as earth, sand, or vermiculite.

SECTION 7. HANDLING AND STORAGE

Wash thoroughly after handling. Remove contaminated clothing and wash before re-use. Do not breathe dust, mist, or vapor. Do not expose eyes, skin, or clothing. Keep container closed tightly. Avoid contact with combustibles. Do not use with metal tools or items. Use with adequate ventilation or respiratory protection. Do not store near combustibles or in direct sunlight. Store in a cool, dry, well-ventilated area away from incompatible substances. Separate from metals, alkali, and organics.

SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Respiratory protection: Wear NIOSH/MESA approved full or half face piece (with goggles) respiratory protective equipment to avoid exposure to vapors above 0.1ppm. A respiratory protection program complying with requirements of 29CFR 1910.134 is recommended.

Ventilation: Where adequate ventilation is not available, use NIOSH approved vapor respirator with dust, fume and mist filters. Local ventilation through fume hoods or laminar flow stations is also preferred. Keep fumes away from strong bases.

Protective gloves: Skin contact should be minimized through use of rubber gloves.

Other protective equipment: Steel tipped shoes/eye wash station/chemical safety chemical retardant clothing.

Eye protection: Safety goggles / face shield

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form :	Syrupy liquid
Appearance :	Colorless
Odor :	Vinegar
pH :	< 2

Ecotoxicity : Biologic effects:

Toxic effect on fish and plankton. Harmful effect due to pH shift. Forms corrosive mixtures with water even when diluted. Does not cause biological oxygen deficit. Hazardous to drinking water supplies.

Fish toxicity: *Gambusia affinis* LC₅₀: 756 mg/L/96 h

Golden orfe/LC₅₀ (96h): > 7500 mg/L

Hazard for drinking water: Fish: LC₅₀ > 1500 mg/L.

SECTION 13. DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose of in accordance with all federal state and local regulations. Send waste to an approved waste disposal facility.

SECTION 14. TRANSPORTATION INFORMATION

Class 8

PG III

UN3264

Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S. (Phosphoric Acid and Acetic Acid)

SECTION 15. REGULATORY

Symbol: C, Corrosive

R-Phrase:

R: Contact with combustible material may cause fire.

R21/22: Harmful in contact with skin and if swallowed.

R35: Causes severe burns.

R41: Risk of serious damage to eyes.

S-Phrases:

S17: Keep away from combustible material.

S23-36/37/39-45 Do not breathe vapor. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 16. OTHER INFORMATION

NFPA Codes:

Health: 3

Flammability: 0

Reactivity: 1

R8: Contact with combustible material may cause fire.

R35: Causes severe burns.

All ingredients of this product are listed on the US TSCA inventory under their parent anhydrous compounds.