

1 Identification of the substance/mixture and of the company

- **Product identifier**
- **Trade name:** SU-8 3000 Series Resists
- **Product number:** Y311075, Y311074, Y311072, Y311060, Y311049
- **Application of the substance / the mixture** Photoresist
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MicroChem Corp.
200 Flanders Road
Westborough, MA 01581 USA
- **Information department:**
Product Safety
Email: productsafety@microchem.com
- **Emergency telephone number:**
MicroChem Corp : 617-965-5511
Chemtrec USA Emergency : 800-424-9300
Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
 Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: SU-8 3000 Series Resists

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Cyclopentanone

Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol]
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Formaldehyde, polymer with (chloromethyl) oxirane and phenol

· Hazard statements

- H226 Flammable liquid and vapor.
 H302+H332 Harmful if swallowed or if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H341 Suspected of causing genetic defects.
 H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P233 Keep container tightly closed.
 P273 Avoid release to the environment.
 P201 Obtain special instructions before use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P363 Wash contaminated clothing before reuse.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
 P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
 P370+P378 In case of fire: Use for extinction: Carbon dioxide.
 P391 Collect spillage.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

15.2 % of the mixture consists of component(s) of unknown toxicity.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2
 Fire = 3
 Reactivity = 0

(Contd. on page 3)

Trade name: SU-8 3000 Series Resists

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.**3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

28906-96-9	Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene) bis[phenol] ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	25-50%
120-92-3	Cyclopentanone ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-25%
9003-36-5	Formaldehyde, polymer with (chloromethyl) oxirane and phenol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	10-25%
244772-00-7	Cycloaliphatic Epoxy Resin ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	10-25%
108-32-7	Propylene carbonate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%
26142-30-3	Poly[oxy(methyl-1,2-ethanediyl)], α-(2-oxiranylmethyl)-ω-(2-oxiranylmethoxy)- ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	1-5%
89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	1-5%
71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	1-5%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane ⚠ Muta. 2, H341; ⚠ Eye Dam. 1, H318; Aquatic Chronic 3, H412	1-5%

4 First-aid measures· **Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air and to be sure call for a doctor.· **After skin contact:**

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Trade name: SU-8 3000 Series Resists

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any drains.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaust at the workplace.
Prevent formation of aerosols.
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Use explosion-proof apparatus / fittings and spark-proof tools.
Protect against electrostatic charges.

(Contd. on page 5)

Trade name: SU-8 3000 Series Resists

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:**
Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.
- **Information about storage in one common storage facility:**
Do not store together with oxidizing and acidic materials.
Do not store together with alkalis (caustic solutions).
Do not store together with amines.
- **Further information about storage conditions:**
Protect from exposure to the light.
Keep container well-sealed in cool, dry location.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-)] (1:2)

ACGIH TLV TWA 0.5 mg/m³

NIOSH IDLH 50 mg/m³

OSHA PEL 0.5 mg/m³

71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

ACGIH TLV TWA: 0.5 mg/m³

NIOSH IDLH 50 mg/m³

OSHA PEL 0.5 mg/m³

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Respiratory equipment:**

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Nitrile rubber, NBR

Butyl rubber, BR

- **Penetration time of glove material** Contact glove manufacture for break-through time.

(Contd. on page 6)

Trade name: SU-8 3000 Series Resists

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Liquid
· Color:	Light yellow
· Odor:	Recognizable
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	130 °C (266 °F)

· Flash point: 30 °C (86 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 430 °C (806 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:	Not determined.
· Upper:	Not determined.

· Vapor pressure: Not determined.

· Density: See other information

· Vapour density: Not determined.

· Evaporation rate: 1.6-2.3 (BuAc=1)

· Solubility in / Miscibility with

· Water: Water miscible No

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· Dynamic: Not determined.

(Contd. on page 7)

Trade name: SU-8 3000 Series Resists

(Contd. of page 6)

· Solvent content:	See Table 1 below			
· VOC content:	See Table 1 below			
· Other information	Name	Sp. Grav.	Vol. (%by wt.)	VOC (g/L)
	SU-8 3005	1.075	48-52	538
	SU-8 3010	1.106	38-42	442
	SU-8 3025	1.143	26-30	320
	SU-8 3035	1.150	24-28	300
	SU-8 3050	1.153	22-27	288

10 Stability and reactivity

- **Reactivity**
- **Chemical stability** Stable under normal use conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Exothermic polymerization.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide
Carbon dioxide
Danger of toxic pyrolysis products.
Corrosive gases/vapors

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

28906-96-9 Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol]		
Oral	LD50	>2000 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50	>5 mg/L (Rat)
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8030 mg/kg (Rat)
Dermal	LD50	4248 mg/kg (Rat)
Inhalative	LC50/4 h	> 5.3 mg/l (Rat)
120-92-3 Cyclopentanone		
Oral	LD50	1820 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)
9003-36-5 Formaldehyde, polymer with (chloromethyl) oxirane and phenol		
Oral	LD50	>2000 mg/kg (Rat)
244772-00-7 Cycloaliphatic Epoxy Resin		
Oral	LD50	>2000 mg/kg (Rat)
26142-30-3 Poly[oxy(methyl-1,2-ethanediyl)], α-(2-oxiranylmethyl)-ω-(2-oxiranylmethoxy)-		
Oral	LD50	>2000 mg/kg (Rat)

(Contd. on page 8)

Trade name: SU-8 3000 Series Resists

(Contd. of page 7)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

- **NTP (National Toxicology Program)**

None of the ingredients are listed.

12 Ecological information

- **Toxicity**

· Aquatic toxicity:	
28906-96-9 Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol]	
100 < LC/EC/IC 50	≤1000 mg/l (algae) ≤1000 mg/l (fish) ≤1000 mg/l (invertebrates)
89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)]	
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)	
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
EC50/48 h	30 mg/l (daphnia magna)
EC50/72 h	255 mg/l (Desmodesmus subscipatus (green algae))
LC50/96 h	55 mg/l (Cyprinus carpio (common carp))
120-92-3 Cyclopentanone	
EC50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea))
	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/48 hr	2950 mg/L (golden orfe)
LC50/96 h	>100 mg/l (fish)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 9)

Trade name: SU-8 3000 Series Resists

(Contd. of page 8)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.**13 Disposal considerations**· **Waste treatment methods**· **Recommendation:**

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.**14 Transport information**· **UN-Number**· **DOT, ADR, IMDG, IATA** UN1866· **UN proper shipping name**· **DOT, ADR**

Resin solution

· **IMDG**

RESIN SOLUTION, MARINE POLLUTANT

· **IATA**

RESIN SOLUTION

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids.

· **Label**

3

· **ADR, IMDG, IATA**· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**· **DOT, ADR, IMDG, IATA**

III

· **Environmental hazards:**· **Marine pollutant:**

Yes

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

33

(Contd. on page 10)

Trade name: SU-8 3000 Series Resists

(Contd. of page 9)

- | | |
|--|--------------------------------|
| · EMS Number: | F-E,S-E |
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | UN1866, Resin solution, 3, III |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

· TSCA (Toxic Substances Control Act):

All ingredients are listed or comply with TSCA regulations.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

· California SCAQMD Rule 443.1 VOC's: See Table 1 - Section 9

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)

Trade name: SU-8 3000 Series Resists

(Contd. of page 10)

· Hazard pictograms



GHS02 GHS07 GHS08 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Cyclopentanone

Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol]
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Formaldehyde, polymer with (chloromethyl) oxirane and phenol

· Hazard statements

H226 Flammable liquid and vapor.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P273 Avoid release to the environment.

P201 Obtain special instructions before use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.

P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Product safety department

· Contact: Mr. Cole

(Contd. on page 12)

Printing date 10/15/2014

Reviewed on 10/15/2014

Trade name: SU-8 3000 Series Resists

(Contd. of page 11)

· Revision History:

The business address of the manufacturer in Section 1 was updated. The hazard classification and precautionary statements for the mixture in Section 2 were revised. The toxicology data in Sections 11 and 12 were revised.

· **Date of preparation / last revision** 10/15/2014 / 5

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA